



Model CSBW-242

### Applications

The Medical Infusion Fluid Warming Cabinet offers safe, efficient warming and storage of sterile fluid infusion packs or bottles, injectables, irrigation solutions, anti-pressure pads and gel positioning equipment. The lower chamber can be used to warm blanket, towels, and bedding materials.

### Application Areas

The warming cabinet is ideal for use in theatre preparation rooms, operation rooms, recovery rooms, intensive care units, renal suites, nurseries, birth rooms, general wards and emergency departments.

### Temperature Control

The warming cabinet employs two independent air distribution and heating systems to achieve temperature uniformity in the two drawer compartments. The PID temperature controller ensures set temperature is achieved accurately and rapidly.

### Design and Construction

- The warming cabinet is constructed of powder-coated mild-steel.
- All sides of the warming cabinet are double wall insulated by insulation foam to maintain temperature stability.
- The cabinet is mounted on four castor wheels.
- Two diagonal wheels can be locked when the cabinet is positioned at duty centre.
- The cabinet top is a stainless steel bench space with rail guard which can be utilized for stock organisation.

### Specifications

Model	CSBW-242
Type	Upper drawer - 2 blankets (85" x 73") Lower drawer - Accommodate 30 x 500ml / 15 x 1000ml round bottles
Preset temperature	42°C
Working temperature range	Ambient + 5°C - 45°C
Safety device	Hi-limit temperature cut-off, drawer-open power cut-off switch, high and low temperature alarms
Electrical loading	1500 watt
Interior dimension	400mm (W) x 362mm (D) x 285mm (H)
Cabinet exterior dimension	705mm (W) x 535mm (D) x 918mm (H)
Air circulation	2 units of fans (1 drawer hot air fan, 1 drawer cross-flow fan)
Drawer material	Powder coated perforated mild steel plate. Full length sliding rail guide with stopper. One drawer can be opened each time.
Housing construction	Double wall foam insulated, powder coated mild steel cabinet mounted on four castor wheels
Electrical	220-240 VAC, 50 Hz, 1.63kW
Weight	75 kg

All specifications are subject to change without prior notice.