



Model BB-6TS

Specifications

6-Place Boiling Bath Model BB-6TS

6-place, rectangular stainless steel water baths. Removable cover has six sets of concentric rings of 105mm x 76mm x 57mm x 41mm diameters. With integral level device and 2 kW heater. Supplied with 3-core cable and plug.

Temperature control	: By thermostat
Operating range	: Ambient to 100°C
Overall dimensions	: 366(W) x 353(D) x 102(H) mm
Bath dimensions	: 341(W) x 243(D) x 98(H)
Electrical	: 240 VAC, 50Hz, 7.7A
Weight	: 5.2 kg



Model BB-12TS

12-Place Boiling Bath Model BB-12/BB-12TS

12-place, rectangular stainless steel water baths. Removable cover has twelve sets of concentric rings of 105mm x 76mm x 57mm x 41mm diameters. With integral level device and 2 kW heater. Supplied with 3-core cable and plug.

Temperature control	: By thermostat (Model BB-12TS)
Operating range	: Ambient to 100°C
Overall dimensions	: 470(W) x 345(D) x 120(H) mm 466(W) x 443(D) x 102(H) mm-TS
Bath dimensions	: 441(W) x 333(D) x 98(H)
Electrical	: 240 VAC, 50Hz, 7.8A
Weight	: 7kg



Model BB-24TS

24-Place Boiling Bath Model BB-24TS

24-place, rectangular stainless steel water baths. Removable cover has twenty four sets of concentric rings of 105mm x 76mm x 57mm x 41mm diameters. With integral level device and 2.5kW heater. With thermostatic control. Supplied with 3-core cable and plug.

Temperature control	: By thermostat
Operating range	: Ambient to 100°C
Overall dimensions	: 727(W) x 542(D) x 126(H) mm
Bath dimensions	: 708(W) x 432(D) x 126(H)
Electrical	: 240 VAC, 50Hz, 9.8A
Weight	: 16 kg

THERMOSTATIC WATER BATH MODEL TWB-6

Large Capacity 6 kW



Model TWB-6

Specifications

The main water tank consists of :

- 870W x 775D x 428H mm c/w 2" rock wool insulation, stainless steel casing for inner tank wall, coated enamel paint for outer wall casing.
- Capacity : 196 litres
- Electrical : 415 VAC, 3 phase, 50Hz
The 6kW heater consists of 2 elements of 3kW each
- Racks : 2 removable heavy duty perforated stainless steel racks with spacing (internal) 100mm between one to another.
- Castor wheel : Heavy duty 2 – 4" type
- The tank comes with inlet and outlet of size 1/2" diameter pipe with valve close/open.
- The main control panel for 6kW thermostatic water bath consists of on/off switches, alarm, timer, temperature indicator and thermal protector.